

## 115N0286 🕑

**Optyma™, OP-HJZ036D39Q** Segment usage: Medium Back Pressure, Refrigerant: R134a; R404A; R448A; R449A; R452A; R513A, Compressor power supply [V/Ph/Hz]: 230/3/60

# **PRODUCT DETAILS**

Gross weight	87 kg	
Net weight	75 kg	
Air flow @ 60Hz [m³/h]	4800 m³/h	
Applications	НВР	
	MBP	
Compressor model	MTZ036-3	
Compressor power supply [V/Ph/	230/3/60	
Hz]		
Condenser type	G8	
Description	OP-HJZ036D39Q	
Electrical code	Q	
Fan current @ 60Hz [A]	2.6 A	
Fan diameter [mm]	457 mm	
Fan power consumption @ 60Hz [W]	889 W	
Fan power supply [V/Ph/Hz]	230/1/60	
Model number	OP-HJZ036D39Q	
No. of phases (compressor)	3	
No. of phases (fan)	1	
Number of fans	1	
Refrigerant	R134a	
	R404A	
	R448A	
	R449A	
	R452A	
	R513A	
Segment usage	Medium Back Pressure	
Technology	Reciprocating	
Туре	Optyma™	
Type designation	Condensing Units	
Version	D39	Optyma - Standard version for Brazil - full E-box

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🗈

### For more information, please use this link to visit the product page on Danfoss Product Store 🗈

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



I.	014L0025 ☑ SGP 12 I, Sight glass, FLARE, 12.00 mm, FLARE, 12.00 mm Inlet connection type: FLARE, Inlet size [mm]: 12.00, Outlet connection type: FLARE, Outlet size [mm]: 12.00
	<b>023Z5041 </b> I2 Hermetic filter drier, DML, 08 cu.in., Steel Inlet connection type: FLARE, Outlet connection type: FLARE, Core Size code: 08 cu.in.
4	061F6050 ☑ Cartridge pressure switch, ACB, 26.50 bar, 18.00 bar Higher activ. pressure [bar]: 26.50, Lower activ. pressure [bar]: 18.00, Reset function: Auto, Contact function: SPST(NC), Pressure connection type: Flare, Pressure connection size: 1/4 in, Electrical connection: Cable, Enclosure rating IP: IP65
Ó	118U601108 Condensing Units Accessories & Spare parts : Receiver Receiver 8L
$\textcircled{\textbf{O}}$	120Z0459 ☑ Compressors Accessories : PTC heater PTC heater 27W
Ũ	120Z0638 ⊠ Compressors Accessories : 175PZ POE lubricant, 175PZ, 1-litre can
1	<b>191U006110 </b> C Condensing Units Accessories & Spare parts : Miscellaneous Suction Accumulator, ASD020H05 5/8 in
Ì	191U007710 Condensing Units Accessories & Spare parts : Oil Separator Oil Separator, Hermetic OSD025H05 5/8in
lmage coming soon	<b>191U0643E </b> ☑ <b>Condensing Units Accessories &amp; Spare parts</b> MCHE + Shroud G8 Hj28-36 Lj96-108

## For more information, please use this link to visit the product page on Danfoss Product Store 🗈

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



e Parts		
	<b>191U127467 ≥</b> Condensing Units Accessories & Spare parts : Kit housing Housing, G8 Optyma <sup>™</sup> Line	
0	191U9906 🗠	
	<b>Condensing Units Accessories &amp; Spare parts : Filter</b> Basket Filter,22 X 28MM APC-983 1 1/4 in	
	6804501V06 ⊵	
Image coming soon	<b>Condensing Units Accessories &amp; Spare parts : Service Valve</b> Rotalock valve V06 1-14R X 1/2 S	
	6804502V09 ⊵	
lmage coming soon	Condensing Units Accessories & Spare parts : Service Valve	
	Rotalock valve V09 1 1/4-12R X 5/8 S	
	MTZ36-3VI 🗵	
	Reciprocating compressor, MTZ36JG3AVE	
	Refrigerant: R134a; R404A; R407A; R407C; R407F; R448A; R449A; R452A; R513A, Segment usage:	
	Refrigeration MT, Compressor power supply [V/Ph/Hz]: 200-230/3/60	

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.