

**115N0324****Optyma™, OP-HGZ160D39Q**

Segment usage: Medium Back Pressure, Refrigerant: R134a; R404A; R448A; R449A; R452A; R513A, Compressor power supply [V/Ph/Hz]: 230/3/60

PRODUCT DETAILS

Gross weight	252 kg	
Net weight	234 kg	
Air flow @ 60Hz [m³/h]	13980 m³/h	
Applications	HBP MBP	
Compressor model	MTZ160-3	
Compressor power supply [V/Ph/Hz]	230/3/60	
Condenser type	Q8	
Description	OP-HGZ160D39Q	
Electrical code	Q	
Fan current @ 60Hz [A]	3.5 A	
Fan diameter [mm]	600 mm	
Fan power consumption @ 60Hz [W]	987 W	
Fan power supply [V/Ph/Hz]	230/1/60	
Model number	OP-HGZ160D39Q	
No. of phases (compressor)	3	
No. of phases (fan)	1	
Number of fans	2	
Refrigerant	R134a R404A R448A R449A R452A R513A	
Segment usage	Medium Back Pressure	
Technology	Reciprocating	
Type	Optyma™	
Type designation	Condensing Units	
Version	D39	Optyma - Standard version for Brazil + full E-box

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**014L0026** [🔗](#)**SGP 16 I, Sight glass, FLARE, 16.00 mm, FLARE, 16.00 mm**

Inlet connection type: FLARE, Inlet size [mm]: 16.00, Outlet connection type: FLARE, Outlet size [mm]: 16.00

**023Z5046** [🔗](#)**Hermetic filter drier, DML, 16 cu.in., Steel**

Inlet connection type: FLARE, Outlet connection type: FLARE, Core Size code: 16 cu.in.

**061F6050** [🔗](#)**Cartridge pressure switch, ACB, 26.50 bar, 18.00 bar**

Higher activ. pressure [bar]: 26.50, Lower activ. pressure [bar]: 18.00, Reset function: Auto, Contact function: SPST(NC), Pressure connection type: Flare, Pressure connection size: 1/4 in, Electrical connection: Cable, Enclosure rating IP: IP65

**118U6015** [🔗](#)**Condensing Units Accessories & Spare parts : Receiver**

Receiver 24L

**120Z0459** [🔗](#)**Compressors Accessories : PTC heater**

PTC heater 27W

**120Z0638** [🔗](#)**Compressors Accessories : 175PZ**

POE lubricant, 175PZ, 1-litre can

**191U006610** [🔗](#)**Condensing Units Accessories & Spare parts : Miscellaneous**

Suction Accumulator, ASD100H11 1 3/8 in

**191U007810** [🔗](#)**Condensing Units Accessories & Spare parts : Oil Separator**

Oil Separator, Hermetic OSD030H07 7/8in

**191U127867** [🔗](#)**Condensing Units Accessories & Spare parts : Kit housing**

Housing, Q8 Optyma™ Line

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts



191U9907 [🔗](#)

Condensing Units Accessories & Spare parts : Filter

Basket Filter,35 X 38MM APC-474 1 3/4 in



193U8025E [🔗](#)

Condensing Units Accessories & Spare parts

MCHE, Q8 Coil + Fan shroud



6804503V04 [🔗](#)

Condensing Units Accessories & Spare parts : Service Valve

Rotalock valve V04 1 1/4-12R X 3/4 S



6804504V05 [🔗](#)

Condensing Units Accessories & Spare parts : Service Valve

Rotalock valve V05 1 1/4-12R X 7/8 S



6804506V02 [🔗](#)

Condensing Units Accessories & Spare parts : Service Valve

Rotalock valve V02 1 3/4 -12R X 1 1/8 S



MTZ160-3VI [🔗](#)

Reciprocating compressor, MTZ160HW3VE

Refrigerant: R134a; R404A; R407A; R407C; R407F; R448A; R449A; R452A; R513A, Segment usage:

Refrigeration MT, Compressor power supply [V/Ph/Hz]: 200-230/3/60

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.