



115N0273 🗷

Optyma™, OP-HJZ022D39N

Segment usage: Medium Back Pressure, Refrigerant: R134a; R404A; R448A; R449A; R452A; R513A, Compressor power supply [V/Ph/Hz]: 230/1/60

PRODUCT DETAILS

Gross weight	64 kg	
Net weight	55 kg	
Air flow @ 60Hz [m³/h]	2400 m³/h	
Applications	НВР	
	MBP	
Compressor model	MTZ022-1	
Compressor power supply [V/Ph/	230/1/60	
Hz]		
Condenser type	D8	
Description	OP-HJZ022D39N	
Electrical code	N	
Fan current @ 60Hz [A]	1.1 A	
Fan diameter [mm]	355 mm	
Fan power consumption @ 60Hz [W]	285 W	
Fan power supply [V/Ph/Hz]	230/1/60	
Model number	OP-HJZ022D39N	
No. of phases (compressor)	1	
No. of phases (fan)	1	
Number of fans	1	
Refrigerant	R134a	
	R404A	
	R448A	
	R449A	
	R452A	
	R513A	
Segment usage	Medium Back Pressure	
Technology	Reciprocating	
Туре	Optyma™	
Type designation	Condensing Units	
Version	D39	Optyma - Standard version for Brazil +
		full E-box

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store $\[mathbb{L}\]$

For more information, please use this link to visit the product page on Danfoss Product Store 🗅

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Spare Parts



014L0022 @

SGP 10 I, Sight glass, FLARE, 10.00 mm, FLARE, 10.00 mm

Inlet connection type: FLARE, Inlet size [mm]: 10.00, Outlet connection type: FLARE, Outlet size [mm]: 10.00



023Z5040 🗷

Hermetic filter drier, DML, 08 cu.in., Steel

Inlet connection type: FLARE, Outlet connection type: FLARE, Core Size code: 08 cu.in.



061F6050 ¹²

Cartridge pressure switch, ACB, 26.50 bar, 18.00 bar

Higher activ. pressure [bar]: 26.50, Lower activ. pressure [bar]: 18.00, Reset function: Auto, Contact function: SPST(NC), Pressure connection type: Flare, Pressure connection size: 1/4 in, Electrical connection: Cable, Enclosure rating IP: IP65



118U600908 12

Condensing Units Accessories & Spare parts: Receiver

Receiver 4L



119-8453A 🗷

Condensing Units Accessories & Spare parts: Starting relay

Starting Relay Type 3ARR3J4A4



120Z0459 🗷

Compressors Accessories: PTC heater

PTC heater 27W



120Z0638 🗷

Compressors Accessories : 175PZPOE lubricant, 175PZ, 1-litre can



191U006010 ₺

Condensing Units Accessories & Spare parts: Miscellaneous

Suction Accumulator, ASD015H04 1/2 in



191U007610 @

Condensing Units Accessories & Spare parts : Oil Separator

Oil Separator, Hermetic OSD020H04 1/2in

For more information, please use this link to visit the product page on Danfoss Product Store 🗷

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Spare Parts



191U127367 🗷

Condensing Units Accessories & Spare parts: Kit housing

Housing, D8 Optyma™ Line



191U9906 🗷

Condensing Units Accessories & Spare parts: Filter

Basket Filter,22 X 28MM APC-983 1 1/4 in



6804500V01 ¹²

Condensing Units Accessories & Spare parts : Service Valve

Rotalock valve V01 1Rx3/8S 38058 R



6804501V06 @

Condensing Units Accessories & Spare parts : Service Valve

Rotalock valve V06 1-14R X 1/2 S



6804502V09 ¹²

Condensing Units Accessories & Spare parts: Service Valve

Rotalock valve V09 1 1/4-12R X 5/8 S



MTZ22-1VI 🗷

Reciprocating compressor, MTZ22JC1BVE

Refrigerant: R134a; R404A; R407A; R407C; R407F; R448A; R449A; R452A; R513A, Segment usage: Refrigeration MT, Compressor power supply [V/Ph/Hz]: 208-230/1/60



193U8024E @

Condensing Units Accessories & Spare parts

MCHE + Packing D8 M19-22