



MTZ32-3VI

${\bf Reciprocating\ compressor,MTZ32JF3AVE}$

Refrigerants: R404A; R407C; R452A; R407A; R134a; R454C; R407F; R513A; R448A; R454A; R455A; R449A, Segment usage: Refrigeration MT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	26.75 Kg
Net weight	25 Kg
Volume	37.73 Liter
EAN	5702428888202
Approval	CE
	UL
	UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	200-230/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	1
Description	MTZ032-3
Diameter [mm]	224 mm
Discharge connection height [mm]	68 mm
Discharge connection pipe size [in]	1/2 in
Discharge connection size [in]	1 in
Drawing number	8501025f
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 ℃
High Side TS Min	-35 °C



PRODUCT DETAILS	
High Side Volume	0.3 L
High value of nominal voltage at	230 V
60Hz [V]	230 V
High value of voltage range at 60Hz	253 V
[V]	255 1
In scope of WEEE and contain	No
batteries	
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 ℃
Low Side TS Min	-35 ℃
Low Side Volume	7.5 L
Low value of nominal voltage at	200 V
60Hz [V]	
Low value of voltage range at 60Hz	180 V
[V]	
LRA	60 A
Max pressure (PS) - high side	29.4 bar
Max pressure (PS) - low side	22.6 bar
MCC	18 A
Model number	MTZ32JF3AVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	0.95 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	385 mm
Packaging length [mm]	330 mm
Packaging weight [Kg]	27 kg
Packaging width [mm]	295 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	MTZ
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	2.5 kg
Refrigerants	R134a
	R404A
	R407A
	R407C
	R407F
	R448A
	R449A
	R452A
	R513A
	R454A
	R454C
Detection along a det COU. I	R455A
Rotational speed at 60Hz [rpm]	3500 rpm



PRODUCT DETAILS

SCIP dossier no.	5a332c1b-1d1b-4998-8115-	
	d0929877ecb4	
Segment usage	Refrigeration MT	
Shipped fittings	Suction and discharge solder sleeves,	
	rotolock nuts, and gaskets	
Shipped instructions	Installation instructions	
Shipped mounting	Mounting kit with grommets, bolts,	
	nuts, sleeves and washers	
Shipped oil	Initial oil charge	
Suction connection height [mm]	263 mm	
Suction connection material	-	
Suction connection pipe size [in]	5/8 in	
Suction connection size [in]	1 1/4 in	
Swept volume [cm3]	53.86 cm ³	
Technology	Reciprocating	
Test Dif [bar] [Max]	30 bar	
Test HP [bar] [Max]	30 bar	
Test LP [bar] [Max]	25 bar	
Torque earth [Nm]	3 N-m	
Torque power [Nm]	3 N-m	
Total height [mm]	356 mm	
Туре	MTZ032	
UK RoHS compliance	Out of scope	
Winding resistance for three-	1.32 Ohm	
phase compressors with identical		
windings [Ohm]		
Proposition 65	WARNING: Cancer and Reproductive	
	Harm	
	www.p65warnings.ca.gov	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories



8156009 🗷

Connector, GASKET

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white



7750009 🗷

Electrical component, Discharge thermostat kit

Discharge thermostat kit



8153007 🗷

Connector, Solder Sleeve

Solder sleeve, P06 (1" rotolock, 1/2" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store 🗅



Accessories



8156131 🗷

Connector, GASKET

Gasket, 1-1/4"



8156130 🗷

Connector, GASKET

Gasket, 1"



8156134 🗷

Electrical component, Terminal box

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp



8153011 🗷

Connector, Solder Sleeve

Solder sleeve, P09 (1-1/4" rotolock, 5/8" ODF)



8156001 🗷

Mounting, Compressor kit

Mounting kit for one and two-cylinder compressor, including 3 grommets, 3 bolts



120Z0575 ¹²

Acoustic hood, Reciprocating

Acoustic hood for one-cylinder compressor

Spare Parts



8168031 🗷

Connector, Rotolock service valve

Rotolock valve, V06 (1" rotolock, 1/2" ODF)



8156145 🗷

Connector, GASKET

Gasket for oil sight glass (black chloroprene)



120Z0459 🗷

Crankcase heater, PTC heater

PTC heater 27W, CE mark, UL

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Spare Parts



7703005 🗷

Connector, Valve set

Valve set, V09 (1-1/4"~5/8"), V06 (1"~1/2")



8168033 🗷

Connector, Rotolock service valve

Rotolock valve, V09 (1-1/4" rotolock, 5/8" ODF)



120Z0638 🗷

Lubricant, 175PZ

POE lubricant, 175PZ, 1-litre can



7773106 🗈

Crankcase heater, Belt heater

Belt type crankcase heater, 54 W, 230 V, CE mark, UL



8156019 🗷

Connector, Sight glass

Oil sight glass with gaskets (black and white)