

**123B1584** [🔗](#)**Reciprocating compressor, GPY14RDa**

Refrigerants: R134a, Segment usage: Refrigeration MT, Compressor power supply [V]: 115/1/60

PRODUCT DETAILS

Gross weight	13.1 Kg
Net weight	12.8 Kg
Volume	13.1 Liter
EAN	5702428584487
Applications	HBP
Auxiliary winding resistance (start winding) for single-phase compressors [Ohm]	4.6
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Colour	Black
Compressor power supply [V]	115/1/60
Configuration code	Single
Cut in current HST 60Hz [A]	44.5 A
Description	GPY14RDa
Discharge connection angle [°]	0°
Discharge connection comments	Rubber plug
Discharge connection diameter [mm]	6.5 mm
Discharge connection height [mm]	121 mm
Discharge connection material	Copper
Economizer	No
Family	P
Frequency [Hz]	60
Height from baseplate [mm]	211 mm
High value of nominal voltage at 60Hz [V]	115 V
High value of voltage range at 60Hz [V]	127 V
In scope of WEEE and contain batteries	No
Low value of nominal voltage at 60Hz [V]	115 V
Low value of voltage range at 60Hz [V]	98 V
LRA HST 60Hz [A]	44.5 A
Main winding resistance for single-phase compressors [Ohm]	1
MCC	10.90 A

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, GPY14RDa

PRODUCT DETAILS

Model number	GPY14RDa
Motor type	CSIR
No. of phases (compressor)	1
Oil quantity [cm3]	400 cm ³
Oil type	POE
Packing format	Single pack
Packing quantity	1
Process connection angle [°]	50 °
Process connection comments	Rubber plug
Process connection diameter [mm]	8.1 mm
Process connection material	Copper
Product group	Hermetic compressors
Product Name Description	Reciprocating compressor P
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	1.15 kg
Refrigerants	R134a
Rotational speed at 60Hz [rpm]	3600 rpm
SCIP dossier no.	cd1d92df-acc4-43d9-8eb6- bb380e61d93f
SCIP dossier product name	GL
Segment usage	Refrigeration MT
Speed Platform	Fixed-speed
Start capacitor capacitance	250 µF
Suction connection angle [°]	20 °
Suction connection diameter [mm]	8.1 mm
Suction connection height [mm]	125 mm
Suction connection material	Copper
Swept volume [cm3]	14.32 cm ³
Technology	Reciprocating
Total height [mm]	217 mm
Type	GPY14
Voltage 60Hz [V]	115 V
Voltage 60Hz [V] [Max]	115 V
Winding temperature short term [°F] [Max]	135 °C
Winding temperature stat [°C] [Max]	115 °C
Proposition 65	WARNING: Cancer and Reproductive Harm www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**123B9707** [↗](#)**Electrical component, Terminal box cover**

Plastic Cover, UL

**123B9703** [↗](#)**Electrical component, Capacitor holder**

Starting Cap. Bracket: Height 95

**123B9138** [↗](#)**Electrical component, Relay**

Relay + Con. Board ECC2 1191-8

**123B9901** [↗](#)**Mounting, Mounting kit**

Mounting Accessories 16mm

Spare Parts

**123B9314** [↗](#)**Electrical component, Start capacitor**

Starting Cap. 250µf/160V+Cover+Cable

**123B9496** [↗](#)**Electrical component, Motor protector**

Protector 9-557

**123B9701** [↗](#)**Electrical component, Cable**

Cord Anchorage

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.