



MTZ64-3VI

Reciprocating compressor, MTZ64HM3AVE

Refrigerants: R404A; R407C; R452A; R407A; R134a; R454C; R407F; R513A; R448A; R454A; R455A; R449A, Segment usage: Refrigeration MT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	41.5 Kg
Net weight	39 Kg
Volume	61.54 Liter
EAN	5702428887960
Approval	CE
	UL
	UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	200-230/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	2
Description	MTZ064-3
Diameter [mm]	288 mm
Discharge connection height [mm]	74 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1 1/4 in
Drawing number	8502012g
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-l, 7(a), 7(c)-l, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 ℃
High Side TS Min	-35 ℃



PRODUCT DETAILS	
High Side Volume	0.6 L
High value of nominal voltage at	230 V
60Hz [V]	
High value of voltage range at 60Hz	253 V
[V]	
In scope of WEEE and contain	No
batteries	
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	16.5 L
Low value of nominal voltage at	200 V
60Hz [V]	
Low value of voltage range at 60Hz	180 V
[V]	
LRA	137 A
Max pressure (PS) - high side	29.4 bar
Max pressure (PS) - low side	22.6 bar
MCC	29 A
Model number	MTZ64HM3AVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	1.8 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	455 mm
Packaging length [mm]	395 mm
Packaging weight [Kg]	40 kg
Packaging weight [mm]	365 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	Reciprocating compressor MTZ
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	5 kg
Refrigerants	R134a
nemgerants	R404A
	R407A
	R407C
	R407F
	R448A
	R449A
	R452A
	R513A
	R454A
	R454A R454C



PRODUCT DETAILS

SCIP dossier no.	9b3fb119-9852-486a-92dd-53aa9c96fd3b
Segment usage	Refrigeration MT
Shipped fittings	Suction and discharge solder sleeves,
	rotolock nuts and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts,
	nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	265 mm
Suction connection material	-
Suction connection pipe size [in]	7/8 in
Suction connection size [in]	1 3/4 in
Swept volume [cm3]	107.71 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	413 mm
Туре	MTZ064
UK RoHS compliance	Out of scope
Winding resistance for three-	0.58 Ohm
phase compressors with identical	
windings [Ohm]	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories



120Z0763 🗹

Mounting, Compressor kitMounting kit 2 cylinder



8156009 🗷

Connector, Gasket

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white



120Z0576 🗹

Acoustic hood, Reciprocating

Acoustic hood for two-cylinder compressor



8156132 🗷

Connector, Gasket

Gasket, 1-3/4"

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Accessories



7750009 🗷

Electrical component, Discharge thermostat kit

Discharge thermostat kit



8153008 🗷

Connector, Solder sleeve

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)



8153013 🗷

Connector, Solder sleeve

Solder sleeve, P07 (1-3/4" rotolock, 7/8" ODF)



8156131 🗷

Connector, Gasket

Gasket, 1-1/4"



8156134 🗷

Electrical component, Terminal box

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp

Spare Parts



8156019 🗈

Connector, Sight glass

Oil sight glass with gaskets (black and white)



120Z0638 🗷

Lubricant, 175PZ

POE lubricant, 175PZ, 1-litre can



8156145 🗷

Connector, Gasket

Gasket for oil sight glass (black chloroprene)



8168032 🗹

Connector, Rotolock service valve

Rotolock valve, V07 (1-3/4" rotolock, 7/8" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Spare Parts



7773109 🗷

Crankcase heater, Belt heater

Belt type crankcase heater, 65 W, 110 V



120Z0459 🗷

Crankcase heater, PTC heater

PTC heater 27W



7703006 🗷

Connector, Valve set

Valve set, V07 (1-3/4"~7/8"), V04 (1-1/4"~3/4")



8168029 🗷

Connector, Rotolock service valve

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)



7773107 🗷

Crankcase heater, Belt heater

Belt type crankcase heater, 65 W, 230 V



120Z0639 12

Lubricant, 175PZ

POE lubricant, 175PZ,2.5L CAN