



121L1286 2

Scroll compressor, HRH044U1LP6

Refrigerants: R410A, Segment usage: Air conditioning, Compressor power supply [V]: 208-230/1/60, Packing format: Single pack

PRODUCT DETAILS

| I HODOCI DE IAIES | |
|-------------------------------------|------------------------|
| Gross weight | 48.03 Kilogram |
| Net weight | 34.88 Kilogram |
| Volume | 0.1 Cubic meter |
| EAN | 5702424062170 |
| Approval | CE |
| | UL |
| | UKCA |
| Auxiliary winding resistance | 0.82 |
| (start winding) for single-phase | |
| compressors [Ohm] | |
| Brand technique | Scroll compressor |
| Capacity control | Fixed speed |
| Capacity of capacitor A | 70 μF |
| Capacity of capacitor B | 161-193 μF |
| CE evaluated | Yes |
| China RoHS compliance | Yes exceed limitations |
| Colour | Blue |
| Compressor power supply [V] | 208-230/1/60 |
| Configuration code | Single |
| Connection type | Brazed |
| Description | HRH044U1 |
| Diameter [mm] | 184 mm |
| Discharge connection height [mm] | 422 mm |
| Discharge connection pipe size [in] | 1/2 in |
| Discharge connection size [in] | 1/2 in |
| Drawing number | 0XR6002B-2 |
| Economizer | No |
| EU RoHS compliance | Yes with exemptions |
| EU RoHS exemption clause | 7(c)-l |
| | 6(a) |
| | 6(a)-l |
| | 6(c) |
| | 7(a) |
| | 8(b) |
| Family | HRH |
| Fitting standard | ODF |
| Frequency [Hz] | 60 |
| Gauge port HP | None |
| Gauge port LP | None |



PRODUCT DETAILS

| PRODUCT DETAILS | |
|--|---------------------------------|
| Gaz equalization | None |
| Glass mounting | None |
| High value of nominal voltage at | 230 V |
| 60Hz [V] | |
| High value of voltage range at 60Hz | 253 V |
| [V] | |
| In scope of WEEE and contain | No |
| batteries | |
| IP protection class | IP22 |
| Length [mm] | 239 mm |
| Low value of nominal voltage at | 208 V |
| 60Hz [V] | |
| Low value of voltage range at 60Hz | 187 V |
| [V] | |
| LRA | 150 A |
| Main winding resistance for single- | 0.32 |
| phase compressors [Ohm] | |
| Max pressure (PS) - high side | 46.1 bar |
| Max pressure (PS) - low side | 31.1 bar |
| MCC | 38 A |
| Model number | HRH044U1LP6 |
| Motor protection | Internal overload protector |
| Network power supply [V/Ph/Hz] | 208-230/1/60 |
| Oil charge [L] | 1.57 L |
| Oil drain | None |
| Oil equalization | None |
| Oil reference | 320HV |
| Oil type | PVE |
| Packing format | Single pack |
| Packing quantity | 1 |
| Phase | 1 |
| Power connections | Spade |
| Product group | Hermetic compressors |
| Product Name Description | Scroll compressor HRH |
| REACH Candidate List substances | Lead (CAS no. 7439-92-1) |
| Refrigerant charge [kg] [Max] | 5.44 kg |
| Refrigerants | R410A |
| Relay model | 3ARR3*3L* |
| RLA | 24.3 A |
| Rotational speed at 60Hz [rpm] | 3500 rpm |
| SCIP dossier no. | 22cfab5a- |
| | a26e-446d-9517-3ee5f4753699 |
| Segment usage | Air conditioning |
| Suction connection height [mm] | 280 mm |
| Suction connection material | |
| | _ |
| | - 7/8 in |
| Suction connection pipe size [in] | 7/8 in |
| Suction connection pipe size [in] Suction connection size [in] | 7/8 in |
| Suction connection pipe size [in] Suction connection size [in] Swept volume [cm3] | 7/8 in 42.61 cm ³ |
| Suction connection pipe size [in] Suction connection size [in] Swept volume [cm3] Technology | 7/8 in 42.61 cm³ Scroll |
| Suction connection pipe size [in] Suction connection size [in] Swept volume [cm3] | 7/8 in 42.61 cm ³ |



PRODUCT DETAILS

| U.S. EPA label | For installations using U.S. EPA |
|----------------------------|---------------------------------------|
| | restricted refrigerants, this product |
| | may be used for servicing |
| | existing equipment only. |
| UK RoHS compliance | Yes with exemptions |
| UK RoHS exemption clause | 19 |
| | 21 |
| | 24 |
| | 12 |
| | 13 |
| | 18 |
| UL evaluated | Yes |
| Viscosity [cP] | 68 cP |
| Voltage of capacitor A [V] | 370 V |
| Voltage of capacitor B [V] | 250 V |
| Width [mm] | 239 mm |
| | |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories



120Z5064 🗷

Mounting, Compressor kit

Mounting kit for one-scroll compressor, including 4 grommets, 4 sleeves, 4 bolts, 4 washers



120Z0051 🗷

Electrical component, Run capacitor

Run capacitor 70 μF



7750009 🗷

Electrical component, Discharge thermostat kit

Discharge thermostat kit



8156130 🗷

Connector, Gasket

Gasket, 1"



120Z5084 🗷

Acoustic hood, Scroll

Acoustic hood

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Accessories



8156009 🗷

Connector, Gasket

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white



8168030 🗷

Connector, Rotolock service valve

Rotolock valve, V05 (1-1/4" rotolock, 7/8" ODF)



120Z0127 🖸

Connector, Solder sleeve adapter set

Solder sleeve adaptor set (1-1/4" rotolock, 7/8" ODF), (1" rotolock, 1/2" ODF)



118U0056 🗷

Electrical component, IP Upgrade kit

IP54 upgrade kit



8153007 🗷

Connector, Solder sleeve

Solder sleeve, P06 (1" rotolock, 1/2" ODF)



8168031 🗷

Connector, Rotolock service valve

Rotolock valve, V06 (1" rotolock, 1/2" ODF)



120Z0400 🗷

Electrical component, Start capacitor

Capacitor 161-193µF 330V



8156131 🗷

Connector, Gasket

Gasket, 1-1/4"



120Z0057 🗷

Crankcase heater, Belt heater

Belt type crankcase heater, 50 W, 230 V

Para más información, use este enlace para visitar la página del producto en Product Store de Danfoss 🗅



Spare Parts



8168030 🗷

Connector, Rotolock service valve

Rotolock valve, V05 (1-1/4" rotolock, 7/8" ODF)



120Z5034 🗷

Lubricant, 320HV

PVE lubricant, 320HV (FVC68D), 1-litre can



120Z5015 🗷

Electrical component, Terminal box

Terminal box



120Z0057 🗷

Crankcase heater, Belt heater

Belt type crankcase heater, 50 W, 230 V



8168031 🗷

Connector, Rotolock service valve

Rotolock valve, V06 (1" rotolock, 1/2" ODF)